

ROOFING NAILS

The Mild Steel Plated roofing nail that has been developed to fulfill the demand for a perfect sealing, inexpensive roofing fastener. The nail has been designed with a sharp point reducing the excessive dimpling effect on metal roofs caused by a less pointed fastener being unable to penetrate quickly and easily.

The seal is a dual composition bonded seal produced from galvanised steel or Zinalume and is bonded to genuine neoprene giving a total O.D. of 16mm. This material has an ultra violet and weatherability performance which exceeds most nominal applications.

SPECIFICATIONS

Length: Standard lengths 60mm and 75mm

Diameter: 4mm

Plating: Hot Dip Galvanized

Assembly: Nails are supplied complete with seals

Packaging: Small cartons of 300 or outers of 1500 (5 cartons of 300)

Approx Quantity Per Kg

60mm 118

75mm 106

ALUMINIUM DRIVE SCREW NAIL

The Aluminium Drive Screw Nail was produced for fixing aluminium roofing. Designed with a twisted shank it has a greater holding power and is less likely to loosen once installed. This nail has been designed for use with our roofing washers.

Note: We recommend that you drill a 3.5-4.0mm pilot hole to insure ease of installation.

SPECIFICATIONS

Length: Standard lengths 65, 75mm

Diameter: 6mm


Head diameter: 10mm

Material: 6061 T⁶ aluminium

Approx Quantity Per Kg

65mm 253

75mm 220

ALUMINIUM CLOUT NAIL

The Alloy Clout Nail was produced for use with many forms of aluminium cladding, however it is also used for holding tags on timber during processing through the saw mill, another common use is holding scrim to bowling greens as the Alloy Clout Nail does not damage mower blades.

SPECIFICATIONS

Length: 30mm

Diameter: 10 gauge

Head diameter: 10mm

Material: 6061 T⁶ aluminium

Approx Quantity Per Kg

1212

